



Head Office:

Vortex Optical Coatings Ltd
Unit 23 Greenfields Business Park
Wheatfield Way
Hinckley
Leicestershire
LE10 1BB

Telephone:
+44 (0)1455 613029

Email:
enquiries@vortexopticalcoatings.co.uk

2.07-2.5µm Bandpass Filter for Non Contact Temperature Measurement

Part Number: BPF-2070-2510-25
Diameter Sample: 25mm **Price:**
£300.00 (Free Shipping)

- Stock 2.07-2.5µm Bandpass Filters "on the shelf" for next day shipping, 25 mm diameter x 0.5 mm thick.
- Vortex's trademark RockArd© deposition technology makes our filters highly durable and suitable for the toughest environments.
- All of our filters exhibit high angular tolerance, extremely low change with temperature and very high resistance to thermal shock.

Suitable Detectors

These filters are suitable to be used in Lead Sulphide (PbS), Indium Gallium Arsenide (InGaAs) and Boltometer type detectors.

Optical Specification

Transmission Peak	90% ave for 2070-2510 nm 50% T at 2050nm and 2550 nm+/-1%
Blocking Range	UV and Visible to 2.0 µm and 2.7-20 µm+
Angle Of Incidence	0°
Substrate	25 mm Diameter, 0.5 mm Thick
Surface Quality	Less than 60-40 Scratch-Dig

Environmental Specification

Adhesion	MIL-C-48497A	Para 4.5.3.1
Humidity	MIL-C-48497A	Para 4.5.3.2
Mild Abrasion	MIL-C-48497A	Para 4.5.3.3
Severe Abrasion	MIL-C-48497A	Para 4.5.5.1
Cleanability	MIL-C-48497A	Para 4.5.4.2
Water Solubility	MIL-C-48497A	Para 4.5.5.3

Do you need a custom quote?

For large volumes and specific enquiries please get in touch!

Spectral Performance

